



Ruc. 2557942-1-827268 DV 8



Fenix Flexo Cold Foil Gold and Silver

Document Purpose : Customs Declaration / Commodity Inspection / Shipping
Document / Product Filing

Item	Standard Specification
Product Name	Flexo Cold Transfer Foil
Material Composition	BOPET base film + Release layer + Vacuum metallized aluminum layer + UV adhesive layer
Total Thickness	0.012 mm (12 μ m)
Available Color	Gloss Gold, Gloss Silver
Thickness Tolerance	± 1 μ m
Standard Roll Core	3-inch (76mm) paper core
Standard Width	320mm / 640mm / 750mm / 1280mm (Custom 50–1500mm available)
Standard Length	500m / 1000m / 2000m / 6000m per roll
Surface Gloss	Gold ≥ 280 GU, Silver ≥ 320 GU
Peel Performance	Smooth release, no filamentation under high-speed printing
Curing Condition	UV curing, 120–180W/cm
Max Processing Speed	200 m/min
Application	UV cold stamping for packaging printing, label printing, paper & plastic surface decoration
Compatible Substrate	Coated paper, cardboard, PE, PP, PET, PVC, synthetic paper

Item	Standard Specification
Storage Condition	Cool & dry environment, 40%–65% RH, ≤35°C
Shelf Life	12 months (sealed original package)
Product Feature	High metallic gloss, fine pattern transfer, high adhesion, no pinhole

Customs Declaration Short Description (Copy Directly)

Flexo Cold Transfer Foil, 0.012mm thickness, BOPET base material, gold/silver metallic color, used for packaging and label UV cold stamping decoration, 12 months shelf life.